TS PRO HULK, 4X1 GAL



Version Revision Date: SDS Number: Date of last issue: -

1.0 2017/10/10 00000003000116099 Date of first issue: 2017/10/10

SECTION 1. IDENTIFICATION

Product name : TS PRO HULK, 4X1 GAL

00000003000116099

Product code : 00000003000116099

Manufacturer or supplier's details

Company name of supplier : Milliken & Company

Address : 920 Milliken Rd

Spartanburg SC 29303

Telephone : +1-864-503-1940 (M-F, 8-5 EST)

E-mail address : sds@milliken.com

Emergency telephone

number

In case of emergency call CHEMTREC US: 1-800-424-9300,

CHEMTREC WORLD: 1-703-527-3887.

Recommended use of the chemical and restrictions on use

Recommended use : Colouring agent

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Serious eye damage : Category 1

GHS label elements

Hazard pictograms

Signal word : Danger

Hazard statements : H318 Causes serious eye damage.

Precautionary statements : **Prevention**:

P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

Other hazards

None known.

TS PRO HULK, 4X1 GAL



Version Revision Date: SDS Number: Date of last issue: -

1.0 2017/10/10 00000003000116099 Date of first issue: 2017/10/10

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Preparation

Hazardous components

Chemical name	CAS-No.	Concentration (%)
alpha-[(1,1,3,3-Tetramethylbutyl)phenyl]-omegahydroxypoly(oxy-1,2-ethanediyl)	9036-19-5	>= 5 - < 10
Kaolin Clay	1332-58-7	>= 5 - < 10
Propylene Glycol	57-55-6	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Causes serious eye damage.

SECTION 5. FIREFIGHTING MEASURES

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

TS PRO HULK, 4X1 GAL



Version Revision Date: SDS Number: Date of last issue: -

1.0 2017/10/10 00000003000116099 Date of first issue: 2017/10/10

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self contained breathing apparatus for fire fighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly of

Keep container tightly closed in a dry and well-ventilated

place.

Electrical installations / working materials must comply with

the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Kaolin Clay	1332-58-7	TWA (Respirable fraction)	2 mg/m3	ACGIH
		TWA	5 mg/m3	NIOSH REL

TS PRO HULK, 4X1 GAL



Version Revision Date: SDS Number: Date of last issue: -

1.0 2017/10/10 00000003000116099 Date of first issue: 2017/10/10

		(Respirable)		
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
Propylene Glycol	57-55-6	TWA	10 mg/m3	US WEEL

Hazardous components without workplace control parameters

Components	CAS-No.
alpha-[(1,1,3,3-	9036-19-5
Tetramethylbutyl)phenyl]-	
omega-hydroxypoly(oxy-1,2-	
ethanediyl)	

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : green

Melting point/freezing point : 32 °F

Boiling point/boiling range : < 230 °F

Flash point : > 212 °F

SECTION 10. STABILITY AND REACTIVITY

TS PRO HULK, 4X1 GAL



Version Revision Date: SDS Number: Date of last issue: -

1.0 2017/10/10 00000003000116099 Date of first issue: 2017/10/10

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : no data available

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

Propylene Glycol:

Acute oral toxicity : LD50 (rat): > 20,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

TS PRO HULK, 4X1 GAL



Version Revision Date: SDS Number: Date of last issue: -

1.0 2017/10/10 00000003000116099 Date of first issue: 2017/10/10

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Propylene Glycol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 40,613 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia dubia): 18,340 mg/l

Exposure time: 48 h Test Type: static test

Persistence and degradability

Components:

Propylene Glycol:

Biodegradability : Biodegradation: 96 %

Exposure time: 64 d

Method: OECD Test Guideline 306

Bioaccumulative potential

Components:

alpha-[(1,1,3,3-Tetramethylbutyl)phenyl]-omega-hydroxypoly(oxy-1,2-ethanediyl):

Partition coefficient: n- :

: log Pow: 2.7

octanol/water

Propylene Glycol:

Partition coefficient: n-

: log Pow: -0.92

octanol/water

TS PRO HULK, 4X1 GAL

Milliken

Version Revision Date: SDS Number: Date of last issue: -

1.0 2017/10/10 00000003000116099 Date of first issue: 2017/10/10

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

Additional ecological

information

: no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

TS PRO HULK, 4X1 GAL



Version Revision Date: SDS Number: Date of last issue: -

1.0 2017/10/10 00000003000116099 Date of first issue: 2017/10/10

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Sodium Hydroxide	1310-73-2	1000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section

302 EHS TPQ.

SARA 313 : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI

Intermediate or Final VOC's (40 CFR 60.489):

Propylene Glycol 57-55-6 3.7 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Sodium Hydroxide 1310-73-2 0.02 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table

117.3:

Sodium Hydroxide 1310-73-2 0.02 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section

California Prop 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

reproductive harm.

SECTION 16. OTHER INFORMATION

Further information

Revision Date : 2017/10/10





Version Revision Date: SDS Number: Date of last issue: -

1.0 2017/10/10 00000003000116099 Date of first issue: 2017/10/10

Please Note: As each customer's use of our product may be different, information we provide, including without limitation, any regulatory information, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.

US / EN